

N32H492xE/xG

N32H492	32 bit ARM Cortex-M4F	240MHz	DSP
1MB	Flash 320KB SRAM	80KB CCM SRAM + 4KB Backup SRAM	3 12bit 4.7Msps
ADC 2	12bit DAC	USB FS Device	USB HS Host/Device
	SDIO FEMC xSPI SDRAM	U(S)ART I2C SPI	CAN-FD Ethernet
		I2S	AES/TDES SHA SM3 SM4
MD5	TRNG	CRC16/32	

CPU

—
—
—

—
—
—
—

—
—
—
—
—

—
—
—
—
—
—
—
—
—
—


—
—

118 GPIOs PD6~PD7 PG9~PG15 9 IO VDDIO

—
—
—
—

—
—
—

1



(1)			(2)	SPQ ⁽³⁾	


- 1.
- 2.
- 3.

		N32H492RE/RG L7		N32H492RE/RG B7		N32H492NE/NG B7		N32H492ME/M GB7		N32H492VE/VG L7		N32H492ZE/ZG L7	
		1.8~3.6V/-											
CPU		ARM Cortex-M4F @240MHz, 300DMIPS											
Flash KB		512	1024	512	1024	512	1024	512	1024	512	1024	512	1024
Total SRAM (KB)	General SRAM	240 ⁽¹⁾											
	CCM SRAM ⁽²⁾	80 ⁽³⁾											
	Backup SRAM	4											
	ATIM	3*16bit											
	GTIM	5*16bit											
		2*32bit ⁽⁴⁾											
		3*16bit ⁽⁵⁾											
	BTIM	2*32bit											
	LPTIM	2*16bit											
	SysTick timer	1											
	WWDG	1*14bit											


3

~ 1 LQFP64

3.1.1 LQFP64



3.1.2 LQFP64







3.2 BGA64

3.2.1 BAG64

3.2.2 BGA64




3.3.2 BGA72




3.4 BGA81

3.4.1 BGA81



3.5 LQFP100


3.5.1 LQFP100



LQFP100



3.6.2 LQFP144



Symbol	millimeters			inches ⁽¹⁾		
	Min	Typ	Max	Min	Typ	Max
0.0630	A	-	-	1.600	-	-
0.0059	A1	0.050	-	0.150	0.0020	-
0.0571	A2	1.350	1.400	1.450	0.0531	0.0551
0.0106	b	0.170	0.220	0.270	0.0067	0.0087
0.7795	D1	0.7874	0.7953	19.800	20.000	20.200
-	D3	0.689	-	17.500	-	-
0.0197	e	-	-	0.500	-	-
0.0236	L	0.0295	0.450	0.600	0.750	0.0
0.0394	L1	-	-	1.000	-	-
3.5°	k	7°	0°	3.5°	7°	0°
-	ccc	0.0031	-	-	0.080	-

4

		1. 2.

